

View Online at <https://aerobasegroup.com/nsn/5306-00-763-2725>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.780 inches

**Fastener Length:**

Between 0.990 inches and 1.010 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.330 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Locking Feature:**

Pellet threads

**Shank Unthreaded Hole Diameter:**

0.062 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.990 inches and 1.010 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Material:**

Steel comp 431

**Material Specification:**

Ams 5628 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0