NSN 5306-00-767-4162

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-767-4162

Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 0.826 inches **Fastener Length:** Between 1.661 inches and 1.691 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.940 inches and 0.950 inches **Extended Washer Thickness:** Between 0.088 inches and 0.108 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches Grip Length: Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams6487 assn standard single material response Surface Treatment: Cadmium **Surface Treatment Specification:** Mil-c-8837, type 2, class 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5306-00-767-4162

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

