NSN 5306-00-769-7532

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-769-7532

Thread Direction	:
Right-hand	
Thread Length:	
Between 1.422 in	ches and 1.428 inches
Fastener Length	
Between 1.865 in	ches and 1.885 inches
Head Style:	
Hexagon extende	d washer
Head Height:	
Between 0.208 in	ches and 0.228 inches
Width Between F	lats:
Between 0.490 in	ches and 0.510 inches
Extended Washe	r Diameter:
Between 0.865 in	ches and 0.885 inches
Extended Washe	r Thickness:
Between 0.047 in	ches and 0.053 inches
Washer Quantity	:
1	
Thread Diameter	:
0.312 inches	
Nonstandard Th	read Pitch Diameter:
+0.2821/+0.2854	inches
Thready Qty Per	Inch (tpi):
24	
Primary Washer	Outside Diameter:
Between 0.865 in	ches and 0.885 inches
Primary Washer	Style:
Flat internal teeth	
Primary Washer	Material Thickness:
Between 0.047 in	ches and 0.053 inches
Material:	
Steel comp 1010	or steel comp 1011 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020
Material Specific	ation:
Qq-s-633 federal	specification all material responses
Surface Treatme	nt:
Cadmium	
Thread Series De	esignator:
Unf	
Shelf Life:	
N/a	
Unit Of Measure	

NSN 5306-00-769-7532

Assembled Washer Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

