NSN 5306-00-771-2548

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-771-2548 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.781 inches and 0.812 inches **Fastener Length:** Between 1.312 inches and 1.328 inches **Head Diameter:** 0.750 inches **Head Height:** Between 0.229 inches and 0.239 inches **Distance From Centerline To Flat:** Between 0.280 inches and 0.290 inches **Shoulder Diameter:** 0.531 inches first shoulder **Shoulder Length:** 0.380 inches first shoulder and 0.390 inches first shoulder **Rib Major Diameter:** Between 0.550 inches and 0.560 inches **Rib Length:** Between 0.318 inches and 0.328 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.062 inches **Thread Diameter:** 0.437 inches Thready Qty Per Inch (tpi): 20 Minimum Yield Strength: 75000 pounds per square inch **Shoulder Shape:** Ribbed first shoulder Material: Steel **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5306-00-771-2548

Ribbed Shoulder Bolt - Page 2 of 2



Fiig:

A003b0