

View Online at <https://aerobasegroup.com/nsn/5306-00-775-5044>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.296 inches and 0.357 inches

**Fastener Length:**

Between 1.618 inches and 1.659 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.120 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.440 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.302 inches and 1.322 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.502 inches first hole and 1.543 inches first hole

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0