## NSN 5306-00-780-1841

Machine Bolt - Page 1 of 2

**Thread Class:** 

Right-hand
Thread Length:
0.531 inches
Fastener Length:

0.656 inches

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5306-00-780-1841

Double hexagon extended washer Head Height: Between 0.244 inches and 0.264 inches Width Between Flats: Between 0.304 inches and 0.313 inches Extended Washer Diameter: Between 0.465 inches and 0.475 inches Extended Washer Thickness: Between 0.465 inches and 0.475 inches Extended Washer Thickness: Between 0.032 inches and 0.052 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches Grip Length: 0.125 inches Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 256000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Hole Configuration Style:
Between 0.244 inches and 0.264 inches  Width Between Flats: Between 0.304 inches and 0.313 inches  Extended Washer Diameter: Between 0.465 inches and 0.475 inches  Extended Washer Thickness: Between 0.032 inches and 0.052 inches  Hole Diameter: 0.046 inches  Thread Diameter: 0.250 inches  Grip Length: 0.125 inches  Hole Quantity: 4  Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Width Between Flats: Between 0.304 inches and 0.313 inches  Extended Washer Diameter: Between 0.465 inches and 0.475 inches  Extended Washer Thickness: Between 0.032 inches and 0.052 inches Hole Diameter: 0.046 inches Thread Diameter: 0.250 inches Grip Length: 0.125 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 256000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Between 0.304 inches and 0.313 inches  Extended Washer Diameter:  Between 0.465 inches and 0.475 inches  Extended Washer Thickness:  Between 0.032 inches and 0.052 inches  Hole Diameter:  0.046 inches  Thread Diameter:  0.250 inches  Grip Length:  0.125 inches  Hole Quantity:  4  Hole Type:  Drilled  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  256000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 54.0 rockwell c
Extended Washer Diameter: Between 0.465 inches and 0.475 inches  Extended Washer Thickness: Between 0.032 inches and 0.052 inches  Hole Diameter: 0.046 inches  Thread Diameter: 0.250 inches  Grip Length: 0.125 inches  Hole Quantity: 4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Between 0.465 inches and 0.475 inches  Extended Washer Thickness:  Between 0.032 inches and 0.052 inches  Hole Diameter:  0.046 inches  Thread Diameter:  0.250 inches  Grip Length:  0.125 inches  Hole Quantity:  4  Hole Type:  Drilled  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  256000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 54.0 rockwell c
Extended Washer Thickness:  Between 0.032 inches and 0.052 inches  Hole Diameter:  0.046 inches  Thread Diameter:  0.250 inches  Grip Length: 0.125 inches  Hole Quantity:  4  Hole Quantity:  4  Hole Type:  Drilled  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  256000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 54.0 rockwell c
Between 0.032 inches and 0.052 inches  Hole Diameter:  0.046 inches  Thread Diameter:  0.250 inches  Grip Length:  0.125 inches  Hole Quantity:  4  Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Hole Diameter:  0.046 inches  Thread Diameter: 0.250 inches  Grip Length: 0.125 inches  Hole Quantity: 4  Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
0.046 inches Thread Diameter: 0.250 inches Grip Length: 0.125 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 256000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Thread Diameter:  0.250 inches  Grip Length: 0.125 inches  Hole Quantity: 4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
0.250 inches  Grip Length: 0.125 inches  Hole Quantity: 4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Grip Length:  0.125 inches  Hole Quantity:  4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
0.125 inches  Hole Quantity: 4  Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Hole Quantity: 4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Hole Type:  Drilled  Features Provided:  Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 256000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Finished head  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Min. Tensile Strength (psi): 256000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Min. Tensile Strength (psi): 256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
256000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
Hardness Rating: 51.0 rockwell c and 54.0 rockwell c
51.0 rockwell c and 54.0 rockwell c
Hole Configuration Style:
Double hexagon flats
Material:
Steel comp h11
Material Specification:
Ams6485 assn standard single material response

## NSN 5306-00-780-1841

Machine Bolt - Page 2 of 2



_	•		_			
<b>ن</b>	ırfa	$\sim$	Irο	o+n	20r	٠.
u	ai ia	uc.	116	аш	161	IL.

Nickel

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0