

View Online at <https://aerobasegroup.com/nsn/5306-00-780-7006>

Thread Class:

1a

Thread Direction:

Right-hand

Thread Length:

Between 0.845 inches and 0.865 inches

Fastener Length:

Between 0.845 inches and 0.865 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.365 inches and 0.385 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

Hole Diameter:

0.070 inches

Shank Unthreaded Hole Diameter:

0.060 inches first hole and 0.080 inches first hole

Thread Diameter:

0.312 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Double hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.735 inches first hole and 0.745 inches first hole

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Precious Material:

Silver

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0