
NSN 5306-00-785-5255

Shear Bolt - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 0.276 inches **Fastener Length:** Between 0.516 inches and 0.557 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.125 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.117 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.240 inches and 0.260 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hole Configuration Style: Hexagon corners Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response or mil-s-6098 military specification single material response Surface Treatment: Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

3

NSN 5306-00-785-5255

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

