

View Online at <https://aerobasegroup.com/nsn/5306-00-788-1643>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.828 inches and 0.843 inches

Fastener Length:

4.070 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.625 inches

Head Height:

0.310 inches

Width Between Flats:

Between 1.428 inches and 1.441 inches

Shoulder Diameter:

1.249 inches

Shoulder Length:

3.100 inches

Shank Unthreaded Hole Diameter:

0.140 inches first hole and 0.147 inches first hole

Concentric Hole Depth:

2.880 inches

Concentric Hole Diameter:

0.750 inches

Thread Diameter:

0.562 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.860 inches first hole

Material:

Steel

Material Specification:

Mil-s-5000 cond c military specification single material response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.