## NSN 5306-00-790-6320

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-790-6320

view Online at https://aerobasegroup.com/nsn/5306-00-790-6320
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.493 inches and 1.596 inches
Fastener Length:
Between 1.896 inches and 1.906 inches
Head Style:
Hexagon extended washer
Head Height:
0.281 inches
Width Between Flats:
Between 0.490 inches and 0.502 inches
Extended Washer Diameter:
0.812 inches
Extended Washer Thickness:
0.062 inches
Shoulder Diameter:
0.373 inches first shoulder and 0.374 inches first shoulder
Shoulder Length:
1.320 inches first shoulder
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
150000 pounds per square inch
Hardness Rating:
34.0 rockwell c and 38.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4130
Material Specification:
Mil-s-6758 military specification single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unf

Unf

## NSN 5306-00-790-6320

Shoulder Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-s-6758 spec.

Shelf Life: