

View Online at <https://aerobasegroup.com/nsn/5306-00-794-8104>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.524 inches

Fastener Length:

2.437 inches

Head Style:

Dee

Head Diameter:

Between 1.990 inches and 2.000 inches

Head Height:

0.188 inches

Distance From Centerline To Flat:

0.875 inches

Shoulder Diameter:

Between 1.2490 inches and 1.2495 inches

Shoulder Length:

Between 1.815 inches and 1.820 inches

Shank Unthreaded Hole Diameter:

0.128 inches first hole

Concentric Hole Diameter:

0.750 inches

Thread Diameter:

1.062 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.280 inches first hole and 2.290 inches first hole

Special Features:

Drill 2 holes for cotter pin 0.128 in. Diameter 90.0 degrees apart and concentric hole surface with chromate treatment mil-b-6868

Material:

Steel comp 4340

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0