

View Online at <https://aerobasegroup.com/nsn/5306-00-794-8104>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.524 inches

**Fastener Length:**

2.437 inches

**Head Style:**

Dee

**Head Diameter:**

Between 1.990 inches and 2.000 inches

**Head Height:**

0.188 inches

**Distance From Centerline To Flat:**

0.875 inches

**Shoulder Diameter:**

Between 1.2490 inches and 1.2495 inches

**Shoulder Length:**

Between 1.815 inches and 1.820 inches

**Shank Unthreaded Hole Diameter:**

0.128 inches first hole

**Concentric Hole Diameter:**

0.750 inches

**Thread Diameter:**

1.062 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.280 inches first hole and 2.290 inches first hole

**Special Features:**

Drill 2 holes for cotter pin 0.128 in. Diameter 90.0 degrees apart and concentric hole surface with chromate treatment mil-b-6868

**Material:**

Steel comp 4340

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0