

View Online at <https://aerobasegroup.com/nsn/5306-00-795-4925>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.125 inches

**Fastener Length:**

2.875 inches

**Head Style:**

Dished hexagon

**Head Height:**

0.656 inches

**Width Between Flats:**

1.125 inches

**Hole Diameter:**

0.094 inches

**Shank Unthreaded Hole Diameter:**

0.250 inches first hole

**Thread Diameter:**

0.875 inches

**Grip Length:**

1.750 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Features Provided:**

Unfinished head

**Thready Qty Per Inch (tpi):**

14

**Hardness Rating:**

28.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.312 inches first hole

**Askewed Head Angle:**

30.0 degrees

**Surface Finish:**

32.0 microinches bearing surface of head

**Special Features:**

Assemble spacer p/n 8159341 on bolt before rolling thread

**Material:**

Steel comp 8642h

**Material Specification:**

Aisi assn standard single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0