

View Online at <https://aerobasegroup.com/nsn/5306-00-795-7992>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.253 inches

Fastener Length:

Between 2.236 inches and 2.258 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Shoulder Diameter:

0.3735 inches first shoulder and 0.3745 inches first shoulder

Shoulder Length:

1.903 inches first shoulder and 1.905 inches first shoulder

Shank Unthreaded Hole Diameter:

0.074 inches first hole and 0.079 inches first hole

Thread Diameter:

0.250 inches

Thread Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.081 inches first hole and 2.103 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response or ams 6300 assn standard 6th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.