NSN 5306-00-800-8014 Externally Relieved Body Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-00-800-8014            |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.344 inches   |
| Fastener Length:   |
| 0.500 inches   |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| 0.125 inches   |
| Width Between Flats:   |
| 0.500 inches   |
| First Diameter From Head:  |
| Between 0.248 inches and 0.250 inches                                    |
| Second Diameter From Head:   |
| 0.137 inches   |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:  |
| 0.156 inches   |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.187 inches   |
| Thread Diameter:   |
| 0.190 inches   |
| Thready Qty Per Inch (tpi):  |
| 24   |
| Minimum Yield Strength:  |
| 35000 pounds per square inch   |
| Externally Relieved Body Diameter Quantity:                              |
| 2  |
| Material:  |
| Steel comp 416   |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Mil-p-12011 military specification single treatment response             |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

## NSN 5306-00-800-8014

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-12011 spec.