## NSN 5306-00-802-6610

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-802-6610 **Thread Direction:** Right-hand **Thread Length:** Between 0.407 inches and 0.412 inches Fastener Length: Between 0.760 inches and 0.780 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches First Diameter From Head: Between 0.250 inches and 0.251 inches **Second Diameter From Head:** 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.293 inches and 0.298 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.348 inches and 0.378 inches **Thread Diameter:** 0.250 inches **Nonstandard Thread Pitch Diameter:** +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 29.0 rockwell c Minimum Yield Strength: 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 2 Material: Steel **Thread Series Designator:** 

Unf Shelf Life: N/a

## NSN 5306-00-802-6610

Externally Relieved Body Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0