

View Online at <https://aerobasegroup.com/nsn/5306-00-806-0703>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.615 inches and 0.635 inches

**Fastener Length:**

Between 0.615 inches and 0.635 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.250 inches and 0.270 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

**Thread Diameter:**

0.190 inches

**Features Provided:**

Finished head

**Nonstandard Thread Pitch Diameter:**

+0.1640/+0.1660 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

142000 pounds per square inch

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Material:**

Stainless steel

**Material Specification:**

Ams 5616 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0