

View Online at <https://aerobasegroup.com/nsn/5306-00-807-1442>

Thread Direction:

Right-hand

Thread Length:

0.473 inches

Fastener Length:

Between 3.090 inches and 3.110 inches

Head Style:

Hexagon

Head Height:

Between 0.209 inches and 0.229 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

First Diameter From Head:

Between 0.372 inches and 0.373 inches

Second Diameter From Head:

Between 0.247 inches and 0.251 inches

Third Diameter From Head:

Between 0.372 inches and 0.373 inches

Fourth Diameter From Head:

Between 0.235 inches and 0.245 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.740 inches and 0.760 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.740 inches and 1.760 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 2.460 inches and 2.470 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 2.517 inches and 2.537 inches

Thread Diameter:

0.187 inches

Nonstandard Thread Pitch Diameter:

+0.2797/+0.2824 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Externally Relieved Body Diameter Quantity:

4

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0