NSN 5306-00-807-9056

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-807-9056 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.377 inches and 0.411 inches **Fastener Length:** Between 1.855 inches and 1.885 inches **Head Style:** Hexagon **Head Height:** 0.060 inches Width Between Flats: 0.625 inches **First Diameter From Head:** 0.438 inches **Second Diameter From Head:** Between 0.355 inches and 0.365 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.294 inches and 1.328 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.444 inches **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 170000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 8630 **Material Specification:** Mil-s-6050, f4 military specification single material response **Surface Treatment:** Nickel **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5306-00-807-9056

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.