NSN 5306-00-808-0213

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-808-0213

Thread Direction: Right-hand Thread Length: Between 0.419 inches and 0.490 inches Fastener Length: Between 0.490 inches and 0.510 inches Head Style: Hexagon Head Height: Between 0.178 inches and 0.198 inches Width Between Flats: Between 0.430 inches and 0.439 inches Hole Diameter: 0.062 inches Thread Diameter: 0.062 inches Hole Quantity: 1 Hole Quantity: Drilled Fastener Provided: Finished head Nonstandard Thread Pitch Diameter: 4.02213/+0.2238 inches Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hexagon flats Material Specification:
Thread Length: Between 0.419 inches and 0.490 inches Fastener Length: Between 0.490 inches and 0.510 inches Head Style: Hexagon Head Height: Between 0.178 inches and 0.198 inches Width Between Flats: Between 0.430 inches and 0.439 inches Hole Diameter: 0.062 inches Thread Diameter: 0.052 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Materiai: Iron alloy 660
ABetween 0.419 inches and 0.490 inchesFastener Length:Between 0.490 inches and 0.510 inchesHead Style:HexagonHead Height:Between 0.178 inches and 0.198 inchesWidth Between Flats:Between 0.430 inches and 0.439 inchesHole Diameter:0.062 inchesThread Diameter:0.052 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:24.0 rockwell c and 36.0 rockwell cHole Configuration Style:Hexagon flatsMateriai:Ion alloy 660
Fastener Length: Between 0.490 inches and 0.510 inches Head Style: Hexagon Head Height: Between 0.178 inches and 0.198 inches Width Between Flats: Between 0.430 inches and 0.439 inches Hole Diameter: 0.062 inches Thread Diameter: 0.052 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Between 0.490 inches and 0.510 inchesHead Style:HexagonHead Height:Between 0.178 inches and 0.198 inchesWidth Between Flats:Between 0.430 inches and 0.439 inchesHole Diameter:0.062 inchesThread Diameter:0.052 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:24.0 rockwell c and 36.0 rockwell cHoe Configuration Style:Hexagon flatsMaterial:Ion alloy 660
Head Style:HexagonHead Height:Between 0.178 inches and 0.198 inchesWidth Between Flats:Between 0.430 inches and 0.439 inchesHole Diameter:0.062 inchesThread Diameter:0.052 inchesHole Quantity:11Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:24.0 rockwell c and 36.0 rockwell cHoezonfiguration Style:Hexagon flatsMaterial:Ion alloy 660
Hexagon Head Height: Between 0.178 inches and 0.198 inches Width Between Flats: Between 0.430 inches and 0.439 inches Hole Diameter: 0.062 inches Hole Diameter: 0.260 inches Hole Quantity: 1 Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c_and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Ion alloy 660
Head Height:Between 0.178 inches and 0.198 inchesWidth Between Flats:Between 0.430 inches and 0.439 inchesHole Diameter:0.062 inchesThread Diameter:0.250 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:24.0 rockwell c and 36.0 rockwell cHole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Between 0.178 inches and 0.198 inchesWidth Between Flats:Between 0.430 inches and 0.439 inchesHole Diameter:0.062 inchesThread Diameter:0.250 inchesHole Quantity:1Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:24.0 rockwell c and 36.0 rockwell cHole Configuration Style:Hexagon flatsMaterial:Iron alloy 660
Width Between Flats: Between 0.430 inches and 0.439 inches Hole Diameter: 0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Between 0.430 inches and 0.439 inches Hole Diameter: 0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 1 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hole Diameter: 0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
0.062 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
0.250 inches Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
1 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
+0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Thready Qty Per Inch (tpi): 28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
28 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hardness Rating: 24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
24.0 rockwell c and 36.0 rockwell c Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hole Configuration Style: Hexagon flats Material: Iron alloy 660
Hexagon flats Material: Iron alloy 660
Material: Iron alloy 660
Iron alloy 660
-
Material Specification:
Ams 5732 assn standard single material response
Precious Material:
Silver
Surface Treatment:
Silver
Silver
Silver Surface Treatment Specification:

NSN 5306-00-808-0213

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

