

View Online at <https://aerobasegroup.com/nsn/5306-00-809-2815>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.595 inches and 0.678 inches

**Fastener Length:**

Between 0.678 inches and 0.698 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.365 inches and 0.385 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.490 inches and 0.510 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Hole Diameter:**

0.062 inches

**Thread Diameter:**

0.312 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Nonstandard Thread Pitch Diameter:**

+0.2797/+0.2824 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

24.0 rockwell c and 36.0 rockwell c

**Minimum Yield Strength:**

85000 pounds per square inch

**Hole Configuration Style:**

Hexagon longitudinal hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0