
NSN 5306-00-809-2815

Machine Bolt - Page 1 of 2

Thread Direction:

Right-hand





Thread Length: Between 0.595 inches and 0.678 inches Fastener Length: Between 0.678 inches and 0.698 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches Hole Diameter: 0.062 inches **Thread Diameter:** 0.312 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Nonstandard Thread Pitch Diameter: +0.2797/+0.2824 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 24.0 rockwell c and 36.0 rockwell c **Minimum Yield Strength:** 85000 pounds per square inch Hole Configuration Style: Hexagon longitudinal hole Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Precious Material:** Silver

NSN 5306-00-809-2815

Machine Bolt - Page 2 of 2

Surface Treatment:

Silver

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

