NSN 5306-00-809-2815

Machine Bolt - Page 1 of 2

Between 0.595 inches and 0.678 inches

Between 0.678 inches and 0.698 inches

Thread Direction:

Thread Length:

Fastener Length:

Double hexagon w/hole

Head Style:

Head Height:

Right-hand



View Online at https://aerobasegroup.com/nsn/5306-00-809-2815

Potuson C 265 inches and C 205 inches	
Between 0.365 inches and 0.385 inches	S
Width Between Flats:	
Between 0.367 inches and 0.376 inches	S
Extended Washer Diameter:	
Between 0.490 inches and 0.510 inches	S
Extended Washer Thickness:	
Between 0.070 inches and 0.080 inches	S
Hole Diameter:	
0.062 inches	
Thread Diameter:	
0.312 inches	
Hole Quantity:	
4	
Hole Type:	
Drilled	
Features Provided:	
Finished head	
Nonstandard Thread Pitch Diameter:	:
+0.2797/+0.2824 inches	
Thready Qty Per Inch (tpi):	
24	
Hardness Rating:	
24.0 rockwell c and 36.0 rockwell c	
Minimum Yield Strength:	
85000 pounds per square inch	
Hole Configuration Style:	
Hexagon longitudinal hole	
Material:	
Iron alloy 660	
Material Specification:	
Ams 5732 assn standard single materia	al response
Precious Material:	
Silver	

NSN 5306-00-809-2815

Machine Bolt - Page 2 of 2



Surface	Treatment:
---------	------------

Silver

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0