

View Online at <https://aerobasegroup.com/nsn/5306-00-813-8050>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.644 inches and 0.694 inches

Fastener Length:

Between 2.041 inches and 2.071 inches

Head Style:

Double hexagon w/hole

Head Height:

0.388 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

0.644 inches

Extended Washer Thickness:

0.091 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.427 inches and 1.447 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas626 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0