## NSN 5306-00-814-0784

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-814-0784

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.640 inches
Fastener Length:
5.672 inches
Head Style:
Hexagon
Head Height:
Between 0.266 inches and 0.297 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.375 inches
Grip Length:
5.000 inches
Hole Quantity:
6
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4037 or steel comp 4130 or steel comp 4140
Material Specification:
Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military
specification 3rd material response or ams 6300 assn standard 4th material response or mil-s-6758 military specification 5th material
response or mil-s-5626 military specification 6th material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

## NSN 5306-00-814-0784

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
<b>Demilitarization:</b> No

Mil-std (military Standard):

Mil-s-6049 spec.