## NSN 5306-00-815-6200



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-815-6200 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.781 inches and 0.931 inches **Fastener Length:** Between 1.641 inches and 1.671 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.940 inches and 0.950 inches **Extended Washer Thickness:** 0.098 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c Material: Steel comp h11 **Material Specification:** 

Ams 6485 assn standard single material response or ams6487 assn standard single material response

**Surface Treatment:** 

Nickel and cadmium

**Surface Treatment Specification:** 

Ams 2416 assn standard all treatment responses

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-00-815-6200

Shear Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0