

View Online at <https://aerobasegroup.com/nsn/5306-00-815-8014>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.260 inches and 0.290 inches

Fastener Length:

1.450 inches

Head Style:

Dee

Head Diameter:

0.700 inches

Head Height:

0.190 inches

Distance From Centerline To Flat:

Between 0.240 inches and 0.270 inches

Shank Unthreaded Hole Diameter:

0.078 inches first hole

First Diameter From Head:

Between 0.300 inches and 0.304 inches

Second Diameter From Head:

Between 0.373 inches and 0.374 inches

Third Diameter From Head:

Between 0.186 inches and 0.196 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.090 inches and 0.120 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.050 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.110 inches and 0.140 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.330 inches first hole

Externally Relieved Body Diameter Quantity:

3

Material:

Steel comp 4140

Material Specification:

Mil-s-5626, cond c4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

0491, type 2, cl a fscm 36659 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.