

View Online at <https://aerobasegroup.com/nsn/5306-00-815-9285>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.406 inches

**Fastener Length:**

Between 1.375 inches and 1.405 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.428 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**Shank Unthreaded Hole Diameter:**

0.066 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.953 inches and 1.015 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

38.0 rockwell c and 42.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.203 inches first hole and 1.233 inches first hole

**Material:**

Steel comp 4340

**Material Specification:**

Asae cond ams 6415 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0