## NSN 5306-00-816-0692

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-816-0692 **Thread Direction:** Right-hand Thread Length: 0.973 inches Fastener Length: 1.593 inches **Head Style:** Round w/wrench flats **Head Diameter:** Between 0.615 inches and 0.635 inches **Head Height:** Between 0.240 inches and 0.260 inches Width Between Flats: Between 0.490 inches and 0.510 inches **First Diameter From Head:** Between 0.309 inches and 0.312 inches **Second Diameter From Head:** Between 0.235 inches and 0.245 inches Third Diameter From Head: Between 0.309 inches and 0.312 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.260 inches and 0.280 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.350 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.620 inches **Thread Diameter:** 0.312 inches **Nonstandard Thread Pitch Diameter:** +0.2797/+0.2824 inches Thready Qty Per Inch (tpi): **Hardness Rating:** 30.0 rockwell c and 36.0 rockwell c **Externally Relieved Body Diameter Quantity:** 3 Material: Stainless steel **Material Specification:** Ams 5616 assn standard single material response

Unf

**Thread Series Designator:** 

## NSN 5306-00-816-0692

Externally Relieved Body Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0