## NSN 5306-00-816-1171

Machine Bolt - Page 1 of 2

**Thread Class:** 

Right-hand

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5306-00-816-1171

| 0.376 inches   |
|--|
| Fastener Length:   |
| Between 0.390 inches and 0.447 inches  |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| 0.188 inches   |
| Width Between Flats:   |
| Between 0.365 inches and 0.377 inches  |
| Hole Diameter:   |
| 0.047 inches   |
| Thread Diameter:   |
| 0.190 inches   |
| Hole Quantity:   |
| 6  |
| Hole Type:   |
| Drilled  |
| Features Provided:   |
| Finished head  |
| Thready Qty Per Inch (tpi):  |
| 32   |
|  |
| Min. Tensile Strength (psi):   |
| Min. Tensile Strength (psi): 180000 pounds per square inch   |
|  |
| 180000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c   |
| 180000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style:  |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style:  Hexagon longitudinal hole  |
| 180000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style:  Hexagon longitudinal hole  Material:  |
| 180000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style:  Hexagon longitudinal hole  Material:  Steel comp 4037   |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment:  |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment: Cadmium and chromate   |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment: Cadmium and chromate  Surface Treatment Specification:   |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment: Cadmium and chromate  Surface Treatment Specification:  Qq-p-416, type 2, class 3 federal specification all treatment responses  |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification all treatment responses  Thread Series Designator:                          |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification all treatment responses  Thread Series Designator: Unjf                     |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification all treatment responses Thread Series Designator: Unjf  Specification Data: |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification all treatment responses  Thread Series Designator: Unjf                     |
| 180000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon longitudinal hole  Material: Steel comp 4037  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification all treatment responses Thread Series Designator: Unjf  Specification Data: |

## NSN 5306-00-816-1171

Machine Bolt - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0