## NSN 5306-00-816-3684

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-816-3684

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.741 inches
Fastener Length:
2.491 inches
Head Style:
Double hexagon w/hole
Head Height:
0.504 inches
Width Between Flats:
Between 0.556 inches and 0.565 inches
Extended Washer Diameter:
0.823 inches
Extended Washer Thickness:
0.123 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
1.750 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas628 professional/industrial association standard
Shelf Life:

N/a

## NSN 5306-00-816-3684

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0