## NSN 5306-00-816-5270

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-816-5270 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** 1.000 inches **Head Style:** Hexagon **Head Height:** Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.725 inches and 0.750 inches **Thread Diameter:** 0.500 inches **Features Provided:** Unfinished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 105000 pounds per square inch Minimum Yield Strength: 65000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 316 **Material Specification:** Qq-s-763 federal specification 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

A003b0

**Demilitarization:** 

## NSN 5306-00-816-5270

Machine Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-dtl-1222j spec.