NSN 5306-00-816-8690

Externally Relieved Body Bolt - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5306-00-816-8690 |
|-------------------------------------------------------------------------|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.281 inches |
| Fastener Length: |
| 1.032 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.188 inches |
| Width Between Flats: |
| 0.500 inches |
| First Diameter From Head: |
| 0.830 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.221 inches |
| Thread Diameter: |
| 0.312 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Hardness Rating: |
| 25.0 rockwell c and 30.0 rockwell c |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 416 |
| Material Specification: |
| Qq-s-763 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| File: |

ı ııg.

A003b0