NSN 5306-00-818-2552

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-818-2552 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.508 inches and 0.523 inches **Fastener Length:** Between 0.713 inches and 0.733 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.450 inches and 0.470 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Shoulder Diameter:** 0.4180 inches first shoulder and 0.4220 inches first shoulder **Shoulder Length:** 0.210 inches first shoulder and 0.225 inches first shoulder **Hole Diameter:** 0.062 inches **Thread Diameter:** 0.312 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Double hexagon flats **Shoulder Shape:** Round first shoulder Material: Nickel alloy **Material Specification:**

Ams 5754 assn standard single material response

Thread Series Designator:

Unc

NSN 5306-00-818-2552

Shoulder Bolt - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0