

View Online at <https://aerobasegroup.com/nsn/5306-00-818-5328>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.547 inches and 0.597 inches

**Fastener Length:**

Between 1.119 inches and 1.149 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.348 inches

**Width Between Flats:**

Between 0.368 inches and 0.377 inches

**Extended Washer Diameter:**

0.526 inches

**Extended Washer Thickness:**

0.082 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.552 inches and 0.572 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Material:**

Steel comp e4340 or steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6098 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response or mil-s-5626 military specification 5th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas625 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.