NSN 5306-00-819-2422

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-00-819-2422

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.568 inches and 0.618 inches
Fastener Length:
Between 1.828 inches and 1.858 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.319 inches and 0.376 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
0.050 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
45.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Product Name:
Navy special project

NSN 5306-00-819-2422

Shear Bolt - Page 2 of 2

A003b0



Material:
Steel comp h11
Material Specification:
Ams6485 assn standard single material response or ams6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas672 assn standard single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: