NSN 5306-00-819-2943

Machine Bolt - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5306-00-819-2943

Thread Class:

| 1111044 014501 |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.782 inches |
| Fastener Length: |
| 5.844 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.265 inches and 0.297 inches |
| Width Between Flats: |
| Between 0.740 inches and 0.752 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| 5.062 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Material: |
| Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140 |
| Material Specification: |
| Mil-b-6812 military specification all material responses |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification all treatment responses |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5306-00-819-2943

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-b-6812 spec.