NSN 5306-00-819-4664

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-819-4664

| Thread Class: | |
|--|--------|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.500 inches | |
| Fastener Length: | |
| 1.500 inches | |
| Head Style: | |
| Double hexagon w/hole | |
| Head Height: | |
| 0.254 inches | |
| Width Between Flats: | |
| Between 0.304 inches and 0.313 inches | |
| Extended Washer Diameter: | |
| Between 0.465 inches and 0.475 inches | |
| Extended Washer Thickness: | |
| 0.042 inches | |
| Hole Diameter: | |
| 0.037 inches | |
| Grip Diameter: | |
| Between 0.2485 inches and 0.2495 inches | |
| Thread Diameter: | |
| 0.250 inches | |
| Grip Length: | |
| 1.000 inches | |
| Hole Quantity: | |
| 4 | |
| Hole Type: | |
| Drilled | |
| Thready Qty Per Inch (tpi): | |
| 28 | |
| Min. Tensile Strength (psi): | |
| 220000 pounds per square inch | |
| Hardness Rating: | |
| 46.0 rockwell c and 50.0 rockwell c | |
| Hole Configuration Style: | |
| Double hexagon longitudinal hole | |
| Material: | |
| Steel comp h11 | |
| Material Specification: | |
| Ame 6/85 agen etandard gingle material response, or ame6/87 agen standard gingle material re | enonco |

NSN 5306-00-819-4664

Shear Bolt - Page 2 of 2

Fiig: A003b0



| Surface Treatment: |
|---|
| Cadmium |
| Surface Treatment Specification: |
| Nas 672 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 56878-ewb22 manufacturers standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |