

View Online at <https://aerobasegroup.com/nsn/5306-00-819-5310>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.290 inches and 0.320 inches

**Fastener Length:**

2.614 inches

**Head Style:**

Hexagon

**Head Height:**

0.280 inches

**Width Between Flats:**

0.938 inches

**Shoulder Diameter:**

Between 0.686 inches and 0.687 inches

**Shoulder Length:**

4.000 inches

**Shank Unthreaded Hole Diameter:**

0.109 inches first hole

**Concentric Hole Diameter:**

Between 0.437 inches and 0.440 inches

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

190000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.269 inches first hole

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626, cond c4 military specification single material response

**Surface Treatment:**

Chromium grip

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.