

View Online at <https://aerobasegroup.com/nsn/5306-00-819-8618>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.633 inches and 0.693 inches

**Fastener Length:**

Between 0.898 inches and 0.928 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.203 inches and 0.235 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.235 inches and 0.265 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

248.0 brinell standard and 341.0 brinell standard

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.678 inches first hole and 0.698 inches first hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams5732 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas1006 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.