Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-821-0935

| Thread Class: | |
|------------------|---|
| 2a | |
| Thread Directio | n: |
| Right-hand | |
| Thread Length: | |
| 1.406 inches | |
| Fastener Lengt | h: |
| 1.500 inches | |
| Head Style: | |
| Hexagon | |
| Head Height: | |
| 0.062 inches | |
| Width Between | Flats: |
| 0.438 inches | |
| First Diameter I | From Head: |
| 0.188 inches | |
| Distance From | Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.094 inches | |
| Thread Diamete | er: |
| 0.250 inches | |
| Thready Qty Pe | er Inch (tpi): |
| 20 | |
| Externally Relie | eved Body Diameter Quantity: |
| 1 | |
| Material: | |
| Steel comp 303 | |
| Material Specifi | ication: |
| Qq-s-763 federa | I specification single material response |
| Surface Treatm | ent: |
| Passivate | |
| Thread Series | Designator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | e: |
| | |
| Demilitarization | 1: |
| No | |
| Fiig: | |
| A003b0 | |