

View Online at <https://aerobasegroup.com/nsn/5306-00-822-3520>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.484 inches and 0.531 inches

**Fastener Length:**

Between 1.672 inches and 1.719 inches

**Head Style:**

Hexagon

**Head Height:**

0.200 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Grip Diameter:**

Between 0.5607 inches and 0.5616 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Single Shear Strength:**

23600 pounds per square inch

**Thread Diameter:**

0.562 inches

**Grip Length:**

1.188 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.484 inches first hole and 1.516 inches first hole

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response or ams 6300 assn standard 6th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Test Data Document:**

76301-macp.S.20201 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.