

View Online at <https://aerobasegroup.com/nsn/5306-00-822-6941>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.905 inches and 0.925 inches

**Fastener Length:**

Between 0.905 inches and 0.925 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.151 inches and 0.161 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.065 inches first hole and 0.072 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.520 inches and 0.540 inches

**Nonstandard Thread Pitch Diameter:**

+0.2213/+0.2238 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.795 inches first hole and 0.815 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel

**Material Specification:**

Ams 5616 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0