

View Online at <https://aerobasegroup.com/nsn/5306-00-822-6941>

Thread Direction:

Right-hand

Thread Length:

Between 0.905 inches and 0.925 inches

Fastener Length:

Between 0.905 inches and 0.925 inches

Head Style:

Hexagon

Head Height:

Between 0.151 inches and 0.161 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.065 inches first hole and 0.072 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 0.520 inches and 0.540 inches

Nonstandard Thread Pitch Diameter:

+0.2213/+0.2238 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.795 inches first hole and 0.815 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel

Material Specification:

Ams 5616 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0