NSN 5306-00-825-0342

Internal Wrenching Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-825-0342

Image Status 2a Thread Direction: Right-hand Thread Length: 0.203 inches Fastener Length: 0.609 inches Head Style: Flat chamfer 0.226 inches Head Direction: 0.226 inches Head Nameter: 0.226 inches Head Note: 0.226 inches Head Note: 0.226 inches Head Note: 0.226 inches Head Note: Diatence From Head: Between 0.089 inches and 0.138 inches First Diameter From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Stries Designator: Nay special project Material: Stainless steel Stries Designator: Unc Stainless steel Stries Designator: Inc	Thread Class:
Firead Direction: Right-hand Thread Length: 0.203 inches Fastener Length: 0.609 inches Head Siyle: Flat charmfer Head Directer: 0.226 inches Head Height: Between 0.128 inches and 0.138 inches First Diameter From Head: Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Herral Drive Style: Hexagon Thread Diameter: 0.139 inches Width Across Flats: 0.109 inches Thread Diameter: 0.139 inches Width Across Flats: 0.139 inches Vidth Across Flats: 0.139 inches Proced Name: Navy special project Materiat: Stainless steel Durface Treatment: Navy special project Materiat: Stainless steel Dirface Treatment: Nav Dird Measure: <t< th=""><th></th></t<>	
Right-hand Tread Length: 0.203 inches Fastenr Length: 0.609 inches Head Syle: Flac chamfer Head Diameter: 0.226 inches Head Diameter: 0.226 inches Head Diameter: 0.226 inches Head Noght: Between 0.128 inches and 0.138 inches First Diameter From Head: Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Hexagon Thread Diameter: 0.138 inches With Across Flats: 0.199 inches Thread Diameter: 1.199 inches Thread Diameter: 1.191 inches Thread State Material: Navy special project Material: Stainless steel State State Material: Navy State Guetter Passivate Thread Steries Designator: <th></th>	
Thread Length:0.203 inchesFastenr Length:0.609 inchesHead Style:Flat chamferHead Dameter:0.226 inchesHead Height:0.226 inchesHeat Normer From Head:Betwen 0.128 inches and 0.138 inchesFirst Diameter From Head:Betwen 0.039 inches and 0.034 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.406 inchesHexagonThread Diameter:0.138 inchesVidth Across Flats:0.139 inchesThread Diameter:0.139 inchesProduct Name:Navy special projectMaterial:Stainless steelStrike Teatment:Product SurfaceIntread Series Designator:UncSheft Life:NaNaDindika:Fired Series Designator:NaNaFired Series Designator:NaFired Series Designator:NaNaFired Series Designator:NaNaSheft Life:NaNaNaSheft Life:NaNaSheft Life:NaSheft Life:NaSheft Life:NaSheft Life:NaSheft Life:NaSheft Life:Sheft Life:Sheft Life:Sheft Life:Sheft Life:<	
0.203 inclustFastener Length:0.609 inclustHead Style:Flat chamferWead Diameter:0.226 inclustHead Height:Between 0.128 inclusts and 0.138 inclustsFirst Diameter From Head:Between 0.039 inclusts and 0.034 inclustsDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.406 inclustsInternal Drive Style:HexagonThread Diameter:0.138 inclusts0.138 inclustsVidth Across Flats:0.109 inclustsThready Oty Per Inclu (tpl):32Product Name:Navy special projectMaterial:Starlises steelSurface Treatment:PasivateInternal Drive Style:UncStarlises steelSurface Treatment:NavNaviNaviNaviFireit Diameter:NaStarlises SteelStarlises Steel<	
Fastener Length: 0.609 inches Head Style: Flat chamfer Head Diameter: 0.226 inches Head Height: Batween 0.128 inches and 0.138 inches First Diameter From Head: Batween 0.089 inches and 0.094 inches Distance From Hagest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Midth Cross Flats: 0.109 inches Starles steel Starles steel Starles steel Starles steel Starles steel Starles Steel Hered Stries Designator: Na Na Na Stell Life: Na Tered Stell Stell Date: Prodict Name: Prodict Name: Prodict Name: Prodict Name: Prodict Name: Prodict Name: Prodit	
0.609 inchesHead Style:Flat chamferHead Diameter:0.226 inchesHead Height:Between 0.128 inches and 0.138 inchesFirst Diameter From Head:Between 0.089 inches and 0.094 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.406 inchesHernal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:0.199 inchesMitterial:SauSauStateres treatment:Navy special projectMaterial:Sainless steelSurface Treatment:PrassivateThread Series Designator:UncSafif Hife:NaNaDiried Measure:NaNaSintilitarization:NoFig:	
Head Style: Flat chamfer Head Diameter: 0.226 inches Head Height: Between 0.128 inches and 0.138 inches First Diameter From Head: Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.199 inches Thready Qty Per Inch (upi): 32 Product Name: Navy special project Material: Stainless steel Stainless steel Diread Series Designator: Unc Shift Itie: Na Na Stainless steel Strates Dired Measure: Na Na Dired Neasure: Na Stainless steel Stainless steel Hered Stries Designator: Na Dired Measure: Na <td></td>	
Flat chamfer Head Diameter: 0.226 inches Head Height: Between 0.128 inches and 0.138 inches First Diameter From Head: Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.199 inches Product Name: Navy special project Material: Stainless steel Surface Treatment: Product Name: Navy special project Material: Product Name: Intread Stells Diffice: Navi Special project Material: Product Name: Intread Stells Diffice: Naviate Thread Stells Material: Product Name: Intread Stells Strike Testensent: Naviate Thread Stells Strike Testensent: <td></td>	
0.228 inches Head Heigh: Between 0.128 inches and 0.138 inches First Diameter From Head: Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Inc Shelf Life: N/va Entite: Na Did Measure: - Theology Descy Christian State District Company Heitie: N/va District Company District Company District Company District Company District Company District Company	
Head Height: Between 0.128 inches and 0.138 inches First Diameter From Head: Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Inc Nav Find: Nave Find: Distance: Inc Stainless steel Surface Treatment: Passivate Thread Measure: Inc Stainless Steel Surface Treatment: Passivate Thread Series Designator: Inc Fig:	Head Diameter:
Between 0.128 inches and 0.138 inches First Diameter From Head: Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Gty Per Inch (tpi): 32 Product Name: Navy special project Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unic Nav Find: Nav Find: Nave Find: Nave Data Series Designator: Unc Shelf Life: Nave Init Of Measure: Init Of Measure Nave <td>0.226 inches</td>	0.226 inches
First Diameter From Head: Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: Na Na Find: Na Find: Na Passivate Fine: Na Shelf Life: Na Na Fine: Na Fine: Fine: Panilitarization: No Fine:	Head Height:
Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Inc Na Diater Treatment: Na Point Life: Na Fine: Na Fine: Point Treat Series Designator: Inc Fine: Na Point Treat Series Designator: Init of Measure:	Between 0.128 inches and 0.138 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:0.406 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Product Name:Navy special projectMaterial:Stainless steelDurface Treatment:PassivateThread Series Designator:UncMaterial:NavyPassivateThread Series Designator:NaNaFile:NaFile:NaFile:NaFile:NaPanilitarization:NoFile:NoFile:NoFile:NoFile:NoFile:NoFile:NoNoFile:NoFile:No	First Diameter From Head:
0.406 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Fig:	Between 0.089 inches and 0.094 inches
Internal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Product Name:Navy special projectMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aDin of Measure:Pomiltarization:NoFig:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
HexagonThread Diameter:0.138 inchesWidth Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Product Name:Navy special projectMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aDin of Measure:Formiltarization:NaFig:	0.406 inches
Inread Diameter:0.138 inchesWidth Across Flats:0.109 inchesInready Qty Per Inch (tpi):32Product Name:Navy special projectMaterial:Stainless steelSurface Treatment:PassivateInread Series Designator:UncShelf Life:N/aInti Of Measure:Paniliatrization:NoFig:	Internal Drive Style:
0.138 inches Width Across Flats: O.109 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Stainless steel Stainless steel Starface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Shelf Life: N/a Fig:	Hexagon
Width Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Product Name:Navy special projectMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:NaUnit Of Measure:Demilitarization:NoFig:	Thread Diameter:
0.109 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Material: Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demiltarization: No Fig:	0.138 inches
Thready Qty Per Inch (tpi):3232Product Name:Navy special projectMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Denilitarization:NoFig:	Width Across Flats:
32 Product Name: Navy special project Material: Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: Demilitarization: No Fig:	0.109 inches
Product Name:Navy special projectNavy special projectMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):
Navy special projectMaterial:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	32
Material:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aDut Of Measure:Demilitarization:NoFig:	Product Name:
Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Navy special project
Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:
Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Pomilitarization: No	Stainless steel
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Passivate
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
A003b0	
	A003b0