

View Online at <https://aerobasegroup.com/nsn/5306-00-826-1306>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.484 inches and 0.515 inches

**Eye Inside Diameter:**

Between 0.190 inches and 0.192 inches

**Shank Length:**

1.000 inches

**Eye Stock Thickness:**

Between 0.183 inches and 0.193 inches

**Overall Length:**

1.875 inches

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

27.0 rockwell c and 32.0 rockwell c

**Distance From Center Of Eye To Shank End:**

1.587 inches

**Eye Outside Width:**

0.500 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Style Designator:**

Round, closed

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.