

View Online at <https://aerobasegroup.com/nsn/5306-00-828-4263>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.894 inches and 0.914 inches

**Fastener Length:**

Between 1.062 inches and 1.072 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.365 inches and 0.385 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.490 inches and 0.510 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.158 inches and 0.168 inches

**Features Provided:**

Finished head

**Nonstandard Thread Pitch Diameter:**

+0.2797/+0.2824 inches

**Thready Qty Per Inch (tpi):**

24

**Surface Finish:**

63.0 microinches bearing surface of head

**Material:**

Steel comp 601

**Material Specification:**

Ams 6304 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0