

View Online at <https://aerobasegroup.com/nsn/5306-00-829-9970>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.169 inches and 1.819 inches

Fastener Length:

Between 5.554 inches and 5.584 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.798 inches and 0.818 inches

Width Between Flats:

Between 0.934 inches and 0.943 inches

Extended Washer Diameter:

Between 1.428 inches and 1.438 inches

Extended Washer Thickness:

Between 0.188 inches and 0.208 inches

Grip Diameter:

Between 0.8730 inches and 0.8740 inches

Thread Diameter:

0.875 inches

Grip Length:

Between 4.365 inches and 4.385 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas634 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.