

View Online at <https://aerobasegroup.com/nsn/5306-00-831-6668>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.842 inches

Fastener Length:

1.967 inches

Head Style:

Hexagon

Head Height:

0.281 inches

Width Between Flats:

Between 0.741 inches and 0.751 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

1.125 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

140000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.734 inches first hole

Material:

Iron alloy 660 or iron alloy

Material Specification:

Ams 5732 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1008 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.