

View Online at <https://aerobasegroup.com/nsn/5306-00-831-6670>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.663 inches

**Fastener Length:**

2.788 inches

**Head Style:**

Hexagon

**Head Height:**

0.219 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

2.125 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.563 inches first hole

**Material:**

Iron alloy 660 or iron alloy

**Material Specification:**

Ams 5735 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas1006 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.